

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

This listing of claims will replace all prior versions, and listings, of all claims in the application.

LISTING OF THE CLAIMS

Claim 1. (Currently amended) A conveyorized horizontal processing line for wet-processing a workpiece (2) having the following facilities: (a) at least one respective transport member (3; 12,18) for the workpiece (2) located above and beneath a conveying path (100) which extends in a horizontal direction of transport (14) and in which the workpiece (2) may be conveyed through the conveyorized processing line ; (b) at least one processing facility (6) for the workpiece (2) which is disposed above the conveying path (100) and forms, together with the at least one transport member (3), one structural component above the conveying path (100); (c) at least one adjusting device for the structural component, the at least one adjusting device having a carrying frame, the adjusting device being operable to raise or lower in a substantially vertical direction and/or pivot said carrying frame, being configured in such a manner that the structural component may be raised or lowered in a substantially vertical direction and/or may be pivoted, and further having a carrying frame, and wherein said structural component is operably held ~~carried~~ by said carrying frame.

Claim 2. (Previously presented) The conveyorized processing line according to claim 1, wherein means are provided by means of which the spacing of the structural component from the workpiece (2) conveyed past said structural component may always

be maintained substantially even.

Claim 3. (Previously presented) The conveyORIZED processing line according to claim 1, wherein at least one sensor is provided to determine the thickness of the workpiece (2).

Claim 4. (Original) The conveyORIZED processing line according to claim 3, wherein the at least one sensor is disposed in the entrance region where the workpiece (2) enters the conveyORIZED processing line.

Claim 5. (Previously presented) The conveyORIZED processing line according to claim 3, wherein a memory is provided for the data concerning the thickness of the workpiece (2).

Claim 6. (Previously presented) The conveyORIZED processing line according to claim 1, wherein a logic for tracking the workpiece (2) in the conveyORIZED processing line and a control system for the at least one adjusting device for the structural component are provided so that, thanks to the logic for tracking the workpiece (2) and to the control system, the height of the structural component is adjustable to the thickness of the workpiece (2) conveyed past said structural component.

Claim 7. (Previously presented) The conveyORIZED processing line according to claim 1, wherein the at least one adjusting device is selected from the group consisting of a motor-driven eccentric shaft (5), a motor-driven threaded spindle (9), a hydraulically or pneumatically driven adjusting device and a motor-driven sheathed cable.

Claim 8. (Original) The conveyORIZED processing line according to claim 7, wherein auxiliary energy for hydraulically driving the at least one adjusting device may

be tapped from at least one pump which is provided on the conveyorized processing line for supplying jet nozzles, spray nozzles or flow nozzles (6) and/or for circulating the bath liquid to ensure the circulation of the liquid in the bath.

Claim 9. (Previously presented) The conveyorized processing line according to claim 1, wherein the at least one processing facility is selected from the group comprising anodes, cathodes, jet nozzles, flow nozzles (6), spray nozzles and suction nozzles for processing fluid and blast and suction nozzles for gases as well as additional guide elements for thin workpieces (2).

Claim 10. (Previously presented) The conveyorized processing line according to claim 1, wherein the at least one transport member (3; 12, 18) is configured to have an elongated shape and extends in a horizontal direction, substantially transverse to the direction of transport(14).

Claim 11. (Original) The conveyorized processing line according to claim 10, wherein the at least one transport member (3) disposed above the conveying path (100) is guided in lateral long hole bearings (11) disposed outside of the conveying path (100).

Claim 12. (Previously presented) The conveyorized processing line according to claim 1, wherein the at least one transport member is selected from the group comprising transport rollers (3; 12) and of transport rolls (18) mounted on an axis.

Claim 13. (Withdrawn) A method of wet-processing a workpiece in a conveyorized horizontal processing line involving the steps of

(a) first acquiring data about the thickness of the workpiece and storing them in a data memory, prior to feeding the workpiece (2) into the processing line,

(b) bringing the workpiece (2) to the conveyORIZED processing line in one direction of transport (14) and passing it through the conveyORIZED processing line on a conveying path (100),

(c) adjusting a structural component, which is comprised of at least one transport member (3; 12, 18) for the workpiece (2) and of at least one processing facility (6) and which is disposed above the conveying path (100) in the conveyORIZED processing line, in such a manner that, as a function of the thickness of the respective workpiece (2) being passed therethrough, the structural component is raised or lowered and/or pivoted relative to the conveying path (100).

Claim 14. (Withdrawn) The method according to claim 13, wherein the spacing of the structural component from the workpiece (2) conveyed past said structural component is always maintained substantially even.

Claim 15. (Withdrawn) The method according to claim 13, wherein the thickness of the workpiece (2) is determined by at least one sensor as it enters the conveyORIZED processing line.

Claim 16. (Withdrawn) The method according to claim 13, wherein the data about the thickness of the workpiece (2) are converted into control signals and wherein said control signals are transmitted to trigger at least one adjusting device (4; 9, 10 ; 5, 26) for raising, lowering and/or pivoting the structural component.

Claim 17. (Withdrawn) The method according to claim 13, wherein the actual location of the workpiece (2) in the conveyORIZED processing line is permanently logically tracked and wherein the structural component is raised, lowered or pivoted as a function

of said location.

Claim 18. (Withdrawn) The method according to claim 13, wherein the structural component is raised, lowered and/or pivoted by way of at least one adjusting device (4; 9, 10; 5, 26) which is driven by means of an actuating drive and is selected from a group comprising motor-driven eccentric shafts (5), motor-driven threaded spindles (9), hydraulic drives, pneumatic drives and motor-driven sheathed cables.

Claim 19. (Withdrawn) The method according to claim 13, wherein auxiliary energy for hydraulically driving the at least one adjusting device (4; 9, 10; 5, 26) is tapped from at least one pump which is provided on the conveyORIZED processing line, said pump supplying the jet nozzles, the spray nozzles or the flow nozzles (6) and/or serving to circulate the bath fluid to ensure the circulation of the fluid in the bath.

Claim 20. (Withdrawn) The method according to claim 13, wherein a set point for the height adjustment of the structural component is determined by measuring the thickness of the workpiece (2) as it is being brought to the conveyORIZED processing line and by logically tracking the workpiece (2) as it is being conveyed through the conveyORIZED processing line.

Claim 21. (Withdrawn) The method according to claim 13, wherein, as the workpiece (2) is being conveyed through the conveyORIZED processing line, the structural component is pivoted in such a manner that the height of the region of the structural component located on the entrance side of the line is adjusted to the thickness of a new workpiece (2) entering the line and wherein, as the workpiece (2) is conveyed further, the structural component is again pivoted in such a manner that the height of the region of the

structural component located on the exit side of the line is now adjusted to the thickness of said entering workpiece (2).

Claim 22. (Withdrawn) The method according to claim 13, wherein the height of the structural component is adjusted to the thickness of the workpiece (2) in such a manner that the force exerted by the at least one transport member (3) onto the respective one of the passing workpieces (2) is limited.